

N 70, BUILT-IN OVEN, 60 X 60 CM, ALU BRUSHED
BLACK ANODIZED
B59CR71D0A



Z12CM10A0 Moussaka pan, enamelled, Z1365WX0 Wireless food thermometer, Z1608CX0 Full ext rails, level independent, pyro, Z1650BE0 Half tray, Z1655CA0 Air Fry & Grill tray, Z166CAX0 SC FlexDesign mounting kit, Z1913X0 Baking Stone, Z9060AY0 (SC)FlexDesign AG 60 Oven 60, Z9060BY0 (SC)FlexDesign BB 60 Oven 60, Z9060DY0 (SC)FlexDesign DB 60 Oven 60, Z9060MY0 (SC)FlexDesign MS 60 Oven 60, Z9075AY0 SC FlexDesign AG 75 WD 14 + 60, Z9075BY0 SC FlexDesign BB 75 WD 14 + 60, Z9075DY0 SC FlexDesign DB 75 WD 14 + 60, Z9075MY0 SC FlexDesign MS 75 WD 14 + 60, Z9105AY0 SC FlexDesign AG 105 60 + 45, Z9105BY0 SC FlexDesign BB 105 60 + 45, Z9105DY0 SC FlexDesign DB 105 60 + 45, Z9105MY0 SC FlexDesign MS 105 60 + 45, Z912AAY0 SC FlexDesign AG 120 WD14 + 60 + 45, Z912ABY0 SC FlexDesign BB 120 WD14 + 60 + 45, Z912ADY0 SC FlexDesign DB 120 WD14 + 60 + 45, Z912AMY0 SC FlexDesign MS 120 WD14 + 60 + 45, Z912BAY0 SC FlexDesign AG 120 60+60, Z990AMY0 SC FlexDesign MS 90 WD 29 + 60

Built-in oven with Slide & Hide - an easy to handle door that gently disappears under the oven. Also with Home Connect - control your oven via the App.

- ✓ Slide & Hide® - An easy to handle door that disappears under the oven for unrestricted access.
- ✓ Circo Therm – smart hot-air solution that lets you bake on up to three levels at once.
- ✓ 3,7" Full Touch TFT Display - Intuitive navigation for easy use and complete control.
- ✓ Pyrolytic Self-Cleaning with Easy Clean: The best duo for optimal cleaning.
- ✓ Favourites - Save and manage the settings of your choice, directly in the Home Connect app!

Color / Material Front:alu brushed black anodized
Built-in / Free-standing: Built-in
Door opening: Drop down
Integrated Cleaning system: Pyrolytic+Hydrolytic
Control Panel Material: Glass
Door Material: Glass
Dimensions: 595x596x548 mm
Dimensions of the packed product (HxWxD):660x650x690 mm
Required niche size for installation (HxWxD): 585-595 x 560-568 x 550 mm
Cavity dimensions: 357 x 480 x 415 mm
Usable volume of cavity: 71 l
Net weight: 39.4 kg
Gross weight: 42.3 kg
EAN code:4242004293545
Connection Rating: 3600 W
Fuse protection: 16 A
Voltage: 220-240 V
Frequency: 50; 60 Hz
Length electrical supply cord: 120 cm



*N 70, BUILT-IN OVEN, 60 X 60 CM, ALU BRUSHED
BLACK ANODIZED
B59CR71D0A*

Heating Functions

- Oven with 15 heating methods: Air fry
- Bread Baking
- Full surface grill
- Dough proving
- CircoTherm gentle
- CircoTherm
- Centre area grill
- Top/Bottom heat
- Top/bottom heating gentle
- Pizza setting
- Low temperature / slow cooking
- Bottom heat
- CircoRoasting
- Pre-Heating
- Keep warm
- Heating methods only via Home Connect App: let rest, preheating
- Temperature range 30 °C - 275 °C
- Cavity volume: 71 l
- Cavity: Shelf support rails, smooth

Racks and Rails

- Number of shelf levels: 4
- Telescopic rails: ComfortFlex shelf supports (includes 1 telescopic rail), Pyrolytic proof

Design

- Deep Black
- Full Touch Control
- Anthracite enamel cavity with 4 shelf positions

Cleaning

- Pyrolytic self-cleaning
- Easy Clean cleaning program
- Full glass inner door - safe touch door

Convenience

- Cooking Assistant
- 3.7" Full Touch TFT Display
- Electronic clock
- Automatic Temperature control for each function
- Temperature control and display on screen
- Residual heat indicator
- Slide&Hide: The fully retractable oven door disappears under the oven cavity. Slide&Hide ovens come with a rotating handle
- Rapid heat-up: Reduce the preheat time at the touch of a button
- Independent oven interior light button, LED lighting
- Cooling fan
- HomeConnect ready on Wi-Fi, Remote diagnostics
- Home Connect helps you to unleash your cooking creativity by allowing you to manage your oven, warming drawer and coffee

machine over your Wi-Fi. Tap via the app, speak to your oven with voice control, and make appliances interact with one another automatically. Home Connect is an ever-growing platform that brings the future to your kitchen

- Software Update Appliance

Accessories

- combination grid, 1 x Universal pan, air fry & grill tray

Safety Features

- Low door temperature, when in use or pyrolytic cleaning
- Quadruple glass door panel glazed, Low door temperature when in use.
- Individual adjustable child lock
- Residual heat indicator
- Safety switch off
- Start button
- door contact switch
- Automatic door lock during pyrolysis




Technical Information

- Length of mains cable: 120 cm
- Nominal voltage: 220 - 240 V
- Total connected load electric: 3.6 KW


Dimensions:

- Appliance dimension (HxWxD): 595 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing

*N 70, BUILT-IN OVEN, 60 X 60 CM, ALU BRUSHED
BLACK ANODIZED
B59CR71D0A*



Installing two appliances on top of each other
Air exchange



A: Air inlet ≥ 200 cm²

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm