


HYBRID™ P3

Weather proof triple rainwater filter with UV


RAINWATER




REGISTERED DESIGN
Patent Pending




FRONT VIEW



SIDE VIEW



TOP VIEW



ISOMETRIC VIEW

Note: All dimensions are in mm.

Hybrid™
Plus P3

Parts Included



Hybrid P3



PL05MP2
Pleated Sediment



CB05MP2
Carbon Block
Taste & Odour



PX01MP2
Polyspun Sediment



User guide



CMB-SP 3-47 pump

Specifications

Ordering Code	Pressure** (kPa)	Max. Flow (Lpm)	Connection	Micron Rating*
HYBRID P3-LF	300-875	50	1" BSP (25mm)	1

Min/Max Temperature: 0-52°C. Protect from freezing.

MAINTENANCE KIT

Ordering Code	Components
---------------	------------

Hybrid™ P series Maintenance Kit Includes:

- 20" MaxiPlus pleated sediment [PL05MP2]
- Taste & odour reducing filter [CB05MP2]
- Solid sediment filter [PX01MP2]
- UV replacement lamp [RL6]
- Replacement quartz sleeve [RQS6]
- Food-grade lubricant, 2 pcs. O-rings

Warranty: Use only genuine Puretec replacement cartridges. 3 year warranty is 1 year parts and labour, 2 years parts only. Excludes consumables.



Warning: Please visit www.puretecgroup.com/instructions to observe essential manufacturer's instructions before use. **Note:** No claims can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change. This document and all its contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systems. This spec sheet has been designed to help make product selection easy. However due to the complex nature of water chemistry, we strongly encourage confirming any product selection with one of our team. We may need to perform a water analysis test to confirm contaminants in water. **Caution:** Do not use with microbiologically unsafe water or water of unknown quality without adequate disinfection before or after the system. **Warranty:** *Warranties in this document cover parts for the period stated and include cover for parts and labour for the first year where applicable, subject to approval. Excludes consumables. **Micron Rating is nominal. Our Water Filtration Specialists can provide you with advice to suit your needs. **Where line pressure exceeds 520kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbing Standards (Ref. AS 3500:2021, Clause 3.3.4). Maximum flow depends on cartridges, vessel, pressure, impurities etc.